

Pneumatic hammer MP-450

Power. Strength. Reliability



Pneumatic hammer

Pneumatic hammer MP-450 is a robust and dependable solution that's perfect for excavators in the II and III size groups, or for repair manipulators. It's versatile enough to tackle a range of tasks, such as demolishing rock and concrete, removing refractory lining and repairing metallurgical units.

Features

Impact frequency

9,6 Hz

Impact energy at a nominal pressure of 0,5 MPa

0,45 kJ

Working temperature

250 C°



- › High-quality alloyed materials provide structural strength and durability. This means that your pneumatic hammer will last longer and require less maintenance.
- › The air-distributing mechanism of the pneumatic hammer provides a high percussion frequency, allowing repairs without destroying the backup lining.
- › Pneumatic hammer is equipped with an easily removable mechanism for fixing tool.
- › Automatic start and shutdown when pressing and releasing the operating tool (chisel) save energy resources and protect the pneumatic hammer structure from destruction.
- › The air-cooled jacket of the body allows for operation in high temperatures, which is especially useful when servicing build up of hot metallurgical ladles.
- › Modern high-quality sealing products are used.

More than **200** pneumatis hammers MP-450 are operated by leaders in the metallurgical industry.

Ukraine

Tel.: +38 067 970 11 50
E-mail: info@dhmgroup.com

Slovakia

Tel.: +421 948 088 597
E-mail: info@dhmgroup.sk

India

Tel.: +91 336 6637 49 49 / 4950
E-mail: i.ray@dhmgroup.com